


Tyče tvaru L rovnoramenné

Equal angle, hot rolled

EN 10056

TDP: EN 10025-2

Značka oceli: S235JR



Rozměry axb [mm]	Tloušťka stěny t [mm]												
	3,0	4,0	5,0	6,0	7,0	8,0	9,0	10,0	12,0	14,0	16,0	18,0	20,0
	Hmotnost [kg/m]												
20x20	0,88	-	-	-	-	-	-	-	-	-	-	-	-
25x25	1,11	1,45	-	-	-	-	-	-	-	-	-	-	-
30x30	1,36	1,78	-	-	-	-	-	-	-	-	-	-	-
35x35	1,60	2,09	-	-	-	-	-	-	-	-	-	-	-
40x40	1,84	2,42	2,97	-	-	-	-	-	-	-	-	-	-
45x45	2,09	2,74	3,38	-	-	-	-	-	-	-	-	-	-
50x50	-	3,06	3,77	4,47	-	-	-	-	-	-	-	-	-
55x55	-	-	4,18	4,95	-	-	-	-	-	-	-	-	-
60x60	-	-	4,57	5,42	-	7,09	-	-	-	-	-	-	-
65x65	-	-	-	5,91	-	7,73	-	-	-	-	-	-	-
70x70	-	-	-	6,39	7,39	8,40	10,6	-	-	-	-	-	-
75x75	-	-	-	6,85	7,94	9,03	-	-	-	-	-	-	-
80x80	-	-	-	7,34	-	9,63	-	11,86	-	-	-	-	-
90x90	-	-	-	8,28	9,61	10,89	12,20	13,43	-	-	-	-	-
100x100	-	-	-	9,26	-	12,18	-	15,04	17,83	-	-	-	-
110x110	-	-	-	-	-	13,43	-	16,60	-	-	-	-	-
120x120	-	-	-	-	-	14,71	-	18,20	21,62	-	-	-	-
130x130	-	-	-	-	-	-	-	-	23,53	27,20	-	-	-
140x140	-	-	-	-	-	-	-	21,38	25,44	29,42	-	-	-
150x150	-	-	-	-	-	-	-	23,00	-	31,60	-	-	-
160x160	-	-	-	-	-	-	-	24,58	29,26	33,87	38,43	-	-
180x180	-	-	-	-	-	-	-	-	33,05	38,30	-	-	-
200x200	-	-	-	-	-	-	-	-	-	42,69	48,50	59,93	-