



Tyče tvaru UPE

UPE beams

EN 1026-2

TDP: EN 10025-2

Značka oceli: **S235JR**

HUTNÍ MATERIÁL

Označení IPE	Jmenovité rozměry					Průřez [mm²]	Hmotnost [kg/m]	Mezní úchytky rozměrů			
	h	b	s	t	r			h	b	s	t
80	80	50	4	7	10	1010	7,90	+2 mm/-2 mm	+1,5 mm/-1,5 mm	±0,5 mm	
100	100	55	4,5	7,5	10,0	1250	9,82				
120	120	60	5,0	8,0	12,0	1540	12,1				
140	140	65	9,0	9,0	12,0	1840	14,5				
160	160	70	5,5	9,5	12,0	2170	17,0				
180	180	75	5,5	10,5	12,0	2510	19,7				
200	200	80	6,0	11,0	13,0	2900	22,8	+2 mm/-2 mm	±0,5 mm	±1,0 mm	
220	220	85	6,5	12,0	13,0	3390	26,6				
240	240	90	7,0	12,5	15,0	3850	30,2				
270	270	95	7,5	13,5	15,0	4480	35,2	+3 mm/-3 mm			±2,0 mm
300	300	100	9,5	15,0	15,0	5660	44,4				
330	330	105	11,0	16,0	18,0	6780	53,2				
360	360	110	12,0	17,0	18,0	7790	61,2	+4 mm/-4 mm	+3 mm/-3 mm		
400	400	115	13,5	18,0	18,0	9190	72,2				