


Tyče tvaru HEB

IPB beams

EN 1025-2

TDP: EN 10025-2

Značka oceli: **S235JR**



HUTNÍ MATERIÁL

Označení HEB	Jmenovité rozměry					Průřez [mm²]	Hmotnost [kg/m]	Mezní úchytky rozměrů				
	h	b	s	t	r			h	b	s	t	
100	100	100	6,0	10,0	12,0	2600	20,4	+4 mm/-2 mm	+3 mm/-3 mm	±1,0 mm	±1,5 mm	
120	120	120	6,5	11,0	12,0	3400	26,7					
140	140	140	7,0	12,0	12,0	4300	33,7					
160	160	160	8,0	13,0	15,0	5430	42,6					
180	180	180	8,5	14,0	15,0	6530	51,2					
200	200	200	9,0	15,0	18,0	7810	61,3					
220	220	220	9,5	16,0	18,0	9100	71,5	+3 mm/-3 mm		+3 mm/-3 mm	±1,0 mm	±1,5 mm
240	240	240	10,0	17,0	21,0	10600	83,2					
260	260	260	10,0	17,5	24,0	11800	93,0					
280	280	280	10,5	18,0	24,0	13100	103,0					
300	300	300	11,0	19,0	27,0	14900	117,0					
320	320	300	11,5	20,5	27,0	16100	127,0					
340	340	300	12,0	21,5	27,0	17100	134,0	+4 mm/-4 mm			+3 mm/-3 mm	±1,5 mm
360	360	300	12,5	22,5	27,0	18100	142,0					
400	400	300	13,5	24,0	27,0	19800	155,0					
450	450	300	14,0	26,0	27,0	21800	171,0					
500	500	300	14,5	28,0	27,0	23900	187,0					
550	550	300	15,0	29,0	27,0	25400	199,0					
600	600	300	15,5	30,0	27,0	27000	212,0	+5 mm/-5 mm	+3 mm/-3 mm			±1,5 mm
650	650	300	16,0	31,0	27,0	28600	225,0					
700	700	300	17,0	32,0	27,0	30600	241,0					
800	800	300	17,5	33,0	30,0	33400	262,0					
900	900	300	18,5	35,0	30,0	37100	291,0					
1000	1000	300	19,0	36,0	30,0	40000	314,0					