


Ocel plochá válcovaná za tepla

Flat steel

EN 10058

TDP: EN 10025-2

Značka oceli: **S235 JR+AR**
S355 JR+AR



HUTNÍ MATERIÁL

Šířka b [mm]	Tloušťka t															Šířka b [mm]
	3,0	4,0	5,0	6,0	8,0	10,0	12,0	15,0	16,0	20,0	25,0	30,0	40,0	50,0	60,0	
15	0,354	-	-	-	-	-	-	-	-	-	-	-	-	-	-	15
20	0,471	0,628	0,785	0,942	1,26	1,57	1,88	2,36	2,51	-	-	-	-	-	-	20
25	0,589	0,785	0,981	1,18	1,57	1,96	2,36	2,94	3,14	-	-	-	-	-	-	25
30	0,707	0,942	1,18	1,41	1,88	2,36	2,83	3,53	3,77	4,71	-	-	-	-	-	30
35	0,825	1,10	1,37	1,65	2,20	2,75	3,30	4,12	4,40	5,50	6,87	-	-	-	-	35
40	0,94	1,26	1,57	1,88	2,51	3,14	3,77	4,71	5,02	6,28	7,85	9,42	-	-	-	40
45	1,06	1,41	1,77	2,12	2,83	3,53	4,24	5,30	5,65	7,07	8,83	10,60	-	-	-	45
50	1,18	1,57	1,96	2,36	3,14	3,93	4,71	5,89	6,28	7,85	9,81	11,80	-	-	-	50
55	1,30	1,73	2,16	2,59	3,45	4,32	5,18	6,48	6,91	8,64	10,80	13,00	-	-	-	55
60	-	1,88	2,36	2,83	3,77	4,71	5,65	7,07	7,54	9,42	11,80	14,10	18,80	-	-	60
65	-	-	2,55	3,06	4,08	5,10	6,12	7,65	8,16	10,20	12,80	15,30	20,40	-	-	65
70	-	-	2,75	3,30	4,40	5,50	6,59	8,24	8,79	11,00	13,70	16,50	22,00	27,50	-	70
75	-	-	2,94	3,53	4,71	5,89	7,07	8,83	9,42	11,80	14,70	17,70	23,60	29,44	-	75
80	-	-	3,14	3,77	5,02	6,28	7,54	9,42	10,00	12,60	15,70	18,80	25,10	31,40	-	80
90	-	-	3,53	4,24	5,65	7,07	8,48	10,60	11,30	14,10	17,70	21,20	28,30	35,30	42,40	90
100	-	-	3,93	4,71	6,28	7,85	9,42	11,80	12,60	15,70	19,60	23,60	31,40	39,30	47,10	100
110	-	-	4,32	5,18	6,91	8,64	10,40	12,95	13,80	17,30	21,60	25,90	34,50	43,20	51,80	110
120	-	-	4,72	5,65	7,54	9,42	11,30	14,10	15,10	18,80	23,60	28,30	37,70	47,10	56,50	120
125	-	-	4,91	5,89	7,85	9,81	11,78	14,72	15,70	19,63	24,53	29,44	39,25	49,07	58,88	125
130	-	-	5,10	6,12	8,16	10,42	12,20	15,30	16,30	20,40	25,50	30,60	40,80	51,00	62,20	130
140	-	-	5,50	6,59	8,79	11,00	13,20	16,50	17,60	22,00	27,50	33,00	44,00	55,00	65,90	140
150	-	-	5,89	7,07	9,42	11,80	14,10	17,70	18,80	23,60	29,40	35,30	47,10	58,90	70,70	150