


Ocel šestihranná tažená za studena

Hexagonal bar drawn

s úchytkami h11

TDP: **EN 10278**

Značka oceli: **S235 JRC+C**
11SMn30+C
 + další



Rozměr šestihranu s	Hmotnost [kg/m]	Průřez [mm ²]	Mezní úchytky přesnosti h11
3,0	0,0610	7,79	0 mm-0,060 mm
3,5	0,0700	10,61	0 mm-0,060 mm
4,0	0,1088	13,86	0 mm-0,060 mm
4,5	0,1377	17,54	0 mm-0,060 mm
5,0	0,1700	21,65	0 mm-0,075 mm
5,5	0,2056	26,20	0 mm-0,075 mm
6,0	0,2447	31,18	0 mm-0,075 mm
7,0	0,3331	42,43	0 mm-0,090 mm
8,0	0,4351	55,43	0 mm-0,090 mm
9,0	0,5507	70,15	0 mm-0,090 mm
10	0,6798	86,60	0 mm-0,090 mm
11	0,8226	104,79	0 mm-0,110 mm
12	0,979	124,71	0 mm-0,110 mm
13	1,149	146,36	0 mm-0,110 mm
14	1,332	169,74	0 mm-0,110 mm
15	1,530	194,86	0 mm-0,110 mm
16	1,740	221,70	0 mm-0,110 mm
17	1,965	250,28	0 mm-0,110 mm
18	2,203	280,59	0 mm-0,130 mm
19	2,454	312,64	0 mm-0,130 mm
21	2,998	381,92	0 mm-0,130 mm
22	3,290	419,16	0 mm-0,130 mm
24	3,916	498,83	0 mm-0,130 mm
26	4,596	585,43	0 mm-0,130 mm
27	4,956	631,33	0 mm-0,130 mm
30	6,118	779,42	0 mm-0,130 mm
32	6,961	886,81	0 mm-0,160 mm
34	7,860	1001,00	0 mm-0,160 mm
36	8,811	1122,40	0 mm-0,160 mm
38	9,817	1250,00	0 mm-0,160 mm
41	11,43	1455,80	0 mm-0,160 mm
46	14,39	1832,50	0 mm-0,160 mm
50	17,00	2165,10	0 mm-0,160 mm
55	20,56	2619,70	0 mm-0,190 mm
60	24,47	3117,70	0 mm-0,190 mm
65	28,72	3659,00	0 mm-0,190 mm
70	33,31	4243,50	0 mm-0,190 mm