


Profil uzavřený obdélníkový

Rectangular tubes

EN 10219

TDP: EN 10219-1

Značka oceli: S235 JRH



Rozměry HxB [mm]	Tloušťka stěny t [mm]								
	1,0	1,5	2,0	3,0	4,0	5,0	6,0	8,0	10,0
	Hmotnost [kg/m]								
20x10	0,44	0,67	0,78	-	-	-	-	-	-
20x15	-	0,80	-	-	-	-	-	-	-
25x10	-	0,80	-	-	-	-	-	-	-
25x15	0,70	0,85	1,18	-	-	-	-	-	-
30x10	0,70	0,85	1,18	-	-	-	-	-	-
30x15	0,67	0,96	1,25	-	-	-	-	-	-
30x18	-	1,08	1,34	-	-	-	-	-	-
30x20	-	1,09	1,41	2,11	-	-	-	-	-
35x20	-	1,20	1,60	-	-	-	-	-	-
40x10	-	-	1,41	-	-	-	-	-	-
40x20	0,95	1,40	1,76	2,60	-	-	-	-	-
40x25	-	1,45	1,84	-	-	-	-	-	-
40x27	-	1,50	1,98	-	-	-	-	-	-
40x30	-	1,60	2,02	3,00	-	-	-	-	-
40x35	-	1,67	2,20	3,17	-	-	-	-	-
50x10	0,95	1,40	1,76	2,60	-	-	-	-	-
50x20	-	1,60	2,02	3,00	-	-	-	-	-
50x25	-	1,67	2,20	3,17	-	-	-	-	-
50x30	-	1,81	2,40	3,60	4,20	-	-	-	-
50x35	-	1,91	2,54	3,72	-	-	-	-	-
50x40	-	-	2,70	3,90	-	-	-	-	-
60x10	-	1,60	2,02	3,00	-	-	-	-	-
60x20	-	1,81	2,40	3,60	4,20	-	-	-	-
60x30	-	-	2,70	3,90	4,85	-	-	-	-
60x35	-	-	2,86	-	-	-	-	-	-
60x40	-	2,20	3,01	4,35	5,50	-	-	-	-
60x50	-	-	-	4,80	-	-	-	-	-
70x30	-	2,20	3,01	4,35	5,50	-	-	-	-
70x35	-	-	3,35	4,50	-	-	-	-	-
70x40	-	-	3,33	4,80	6,08	7,20	-	-	-
70x50	-	-	3,58	5,30	7,20	8,17	-	-	-
80x20	-	-	2,93	4,25	-	-	-	-	-
80x30	-	-	3,33	4,80	6,08	7,20	-	-	-
80x35	-	-	3,49	5,06	-	-	-	-	-
80x40	-	-	3,77	5,40	7,20	8,15	-	-	-
80x50	-	-	3,90	5,80	7,53	8,92	10,40	12,60	-
80x60	-	-	4,20	6,20	8,50	9,70	11,30	13,80	-
90x40	-	-	3,90	5,80	7,53	8,92	10,40	12,60	-
90x50	-	-	4,20	6,20	8,50	9,70	11,30	13,80	-
100x20	-	-	3,77	5,40	-	-	-	-	-
100x30	-	-	3,90	5,80	7,53	8,92	10,40	12,60	-
100x40	-	-	4,20	6,20	8,50	9,70	11,30	13,80	-
100x50	-	-	4,50	6,70	8,78	10,50	12,30	15,10	-
100x60	-	-	4,82	7,20	9,50	11,30	13,20	16,40	-
100x80	-	-	5,45	8,01	10,50	12,80	15,10	18,90	22,40

pokračování >