


Trubky konstrukční svařované

Round tubes welded

EN 10219-2

TDP: EN 10219-1

Značka oceli: S235JRH



Vnější průměr D [mm]	Případné označení v palcích	Tloušťka stěny t [mm]								
		1,0	1,5	2,0	3,0	4,0	5,0	6,0	8,0	10,0
		Hmotnost [kg/m]								
5,0		0,099	-	-	-	-	-	-	-	-
8,0		0,173	0,240	0,296	-	-	-	-	-	-
10,0		0,222	0,314	0,395	-	-	-	-	-	-
12,0		0,271	0,388	0,49	-	-	-	-	-	-
14,0		0,321	0,462	0,592	-	-	-	-	-	-
15,0		0,345	0,499	0,641	-	-	-	-	-	-
16,0		0,370	0,536	0,691	-	-	-	-	-	-
17,2	3/8"	0,410	0,600	0,750	-	-	-	-	-	-
18,0		0,419	0,610	0,789	-	-	-	-	-	-
20,0		0,469	0,684	0,888	-	-	-	-	-	-
21,3	1/2"	0,501	0,732	0,952	1,35	1,71	-	-	-	-
22,0		0,518	0,758	0,986	-	-	-	-	-	-
25,0		0,592	0,869	1,13	1,63	-	-	-	-	-
26,9	3/4"	0,639	0,940	1,23	1,77	2,26	-	-	-	-
28,0		0,666	0,980	1,28	1,85	-	-	-	-	-
30,0		0,715	1,050	1,38	2,00	2,56	-	-	-	-
32,0		0,765	1,130	1,48	2,15	-	-	-	-	-
33,7	1"	0,806	1,190	1,56	2,27	2,93	3,45	-	-	-
35,0		0,838	1,240	1,63	2,37	3,06	-	-	-	-
38,0		0,912	1,350	1,78	2,59	3,35	-	-	-	-
40,0		0,96	1,420	1,87	2,74	3,55	4,32	-	-	-
42,4	5/4"	1,030	1,510	1,99	2,91	3,79	4,61	-	-	-
45,0		1,075	1,610	2,12	3,11	4,04	-	-	-	-
48,3	6/4"	1,166	1,730	2,28	3,35	4,37	5,34	-	-	-
50,0		1,210	1,790	2,37	3,48	4,54	5,55	-	-	-
51,0		1,235	1,830	2,42	3,55	4,64	-	-	-	-
57,0		1,380	2,050	2,71	3,99	5,23	-	-	-	-
60,3	2"	1,450	2,180	2,88	4,24	5,55	6,82	8,03	-	-
63,5		1,550	2,300	3,03	4,44	5,85	7,21	8,51	-	-
70,0		-	2,530	3,35	4,96	6,51	8,01	9,47	-	-
76,1	2 1/2"	-	2,760	3,65	5,41	7,11	8,77	10,40	13,40	-
80,0		-	2,900	3,85	5,70	7,50	9,25	10,90	14,20	-
83,0		-	3,010	4,00	5,92	7,79	9,62	11,40	14,80	-
88,9	3"	-	3,230	4,29	6,36	8,38	10,30	12,30	16,00	19,50
101,6	3 1/2"	-	-	4,91	7,29	9,63	11,90	14,10	18,50	22,60
108,0		-	-	5,23	7,77	10,30	12,70	15,10	19,70	24,20
114,3	4"	-	-	5,54	8,23	10,90	13,50	16,00	21,00	25,70
121,0		-	-	5,87	8,73	11,50	14,30	17,00	22,30	27,40
127,0	4 1/2"	-	-	6,17	9,17	12,10	15,00	17,90	23,50	28,90
133,0		-	-	6,46	9,62	12,70	15,80	18,80	24,70	30,30

pokračování >